



TECHNICAL DATA

		ARBOS 7260
ENGINE		
Model		Tier IV Final
Cylinders/Displacement	N°/cm³	FPT 6/6700
Injection system		2000 bar Common Rail
Valves		24 valves
Max. homologated power (2000/25/CE)	hp/KW	260/191
Max. torque	Nm	1050
Cooling		Liquid
Engine control		Electronic
Silencer		Underhood with exhaust on cab upright
After treatment system		DOC+ SCR integrated on rear side pillar
Ad-Blue fuel tank capacity	l	50
Fuel tank capacity	l	350 (OPT 450)
TRANSMISSION ADVANCED		
Clutch		WET clutch
Gearstep		5
Range		2
Creepers		STD
Speed	FWD+REV	60 + 15 (with 4 "IMPLEMENT Powershift" gears underload)
Max. speed		50 kph (40 kph eco at 1840 rpm)
Shuttle		Powershuttle
4WD		Electrohydraulic engagement
Differential lock		100% diff lock with electrohydraulic engagement
Rear P.T.O		
Clutch		WET clutch
Speed	rpm	540Eco - 1000 - 1000Eco
Operation		electrohydraulic
BRAKES AND STEERING		
Braking system		Wet disks, 4WD engagement
Trailer braking		hydraulic braking system pneumatic braking system
Hydrostatic steering		STD
Steering angle		55°
Front Axle		with independent suspensions

ARBOS 7260**HYDRAULIC LIFT**

Rear lift		Electronic
Pump delivery	l/min	160 l/min load sensing + 40 l/m
Spool Valves	rear	5 electrohydraulic std + Power Beyond
	front	3 mid-mounted electrohydraulic
Max. lifting capacity at ball hitch	kg	10500

DRIVING POSITION

Cab features		Original sound-proofed, with silent block mounted platform, high visibility roof with rounded glass, up to 8 worklights (4 rear + 4 front) + telescopic rear-view mirrors
Cab conditioning		Air conditioning
Instruments		TFT 7" digital display
Driver's seat		Pneumatic suspension, safety belt

DIMENSIONS AND WEIGHTS: with rear tyres

Weight	kg	8500
Max. admissible load	kg	14000
Wheelbase	mm	2950
Max. tyres		710/60 R42

