



ZL60H WHEEL LOADER SPECIFICATIONS

- Equipped with reliable original Cummins engine
- Kick-down switch allows better efficiency & easy operation
- Famous original GRAZIANO wet type axle with multi-disc limited-slip differentials deliver maximum traction in changing traction conditions
- Reliable ZF transmission case and torque converter
- Bucket automatic leveling ability
- Combined seal cylinder obtains high seal performance and more reliability

Overall Dimension		
1	Length(with bucket on ground)	8280(mm)
2	Width(to outside of wheels)	2897(mm)
3	Bucket width	3064(mm)
4	Height(To the top of the cab)	3565(mm)
5	Wheel base	3300(mm)
6	Tyre tread	2300(mm)
7	Min. ground clearance	460(mm)

Main Technical Specification		
1	Rated load	6000(Kg)
2	Operating weight	18600kg
3	Rated bucket capacity	3.5(m ³)
4	Max. breakout force	186KN
5	Max. Driving force	180 KN
6	Max. dump clearance	3028(mm)
7	Dump reach	1229(mm)
8	Dump angle at any position	≥ 45°
9	Digging depth(with bucket bottom horizontal)	212(mm)
10	Min. turning radius	
	(1)Outside of bucket	6870(mm)
	(2)Outside of rear wheel	6400(mm)
11	Pivot angle frame	38±1°
12	Oscillating angle of rear axle	±12°
13	Lifting time of bucket	6.0(sec.)
14	Lowering time of bucket	3.9(sec.)
15	Dumping time	1.9(sec.)
16	Traveling speed(Km/h)	
	(1)1st gear (Forward & reverse)	6.6
	(2)2nd gear (Forward & reverse)	11.7
	(3)3rd gear (Forward & reverse)	23.1
	(4)4th gear (Forward)	36
Diesel engine		

1	Model	Cummins 6CTAA8.3-C240 (TIER2)	SHANGCHAI C6121ZG20 (TIER1)
2	Type	Direct injection. Turbocharged. Water cooling	
3	Rated output	179kW	174kW
4	Inter-bore of cylinder/stroke	114/135(mm)	121/152 (mm)
5	Total exhaust of cylinder	8.3(L)	10.5L
6	Model of starting motor	Delco-Remy 42MT	4N3181
7	Power of start motor	8.2(KW)	7.5(KW)
8	Voltage of starting motor	24(V)	24V
9	Rated speed	2200rpm	2200rpm
10	Max. Torque	1146(N.m)	918.5(N.m)
11	Starting type	Electric	Electric
12	Min. specific fuel consumption	205(g/Kw.h)	238g/Kw.h
13	Engine specific oil consumption	0.9-1.6(g/Kw.h)	0.95-1.77(g/Kw.h)
14	Net weight	617(Kg)	960Kg
Transmission System			
1. Torque Converter			
1	Type	3-element.single stage	
2	Torque ratio	2.55	
3	Max. Dia. of flow path	340(mm)	
4	Cooling type	Pressure oil circulating	
2. Gear Box			
1	Model	ZF 4WG200	
2	Type	Fixed shaft. Power shift	
3	Gear shift position	4 Forward and 3 reverse gears	

3. Axle and Tire			
1	Type of main reducer		single stage
2	Gear ratio of main reducer		4.444
3	Type of final reducer		single stage planetary
4	Gear of ratio of final reducer		5.167
5	Total gear ratio		22.963
6	Size of tyre		23.5-25 -16PR (L-3)
Working Device Hydraulic System			
1	Model of oil pump		P257-G80367ZCA6/P124-G20LIG
2	System pressure		20(MPa)
3	Model of distribution valve		HUSCO 7130-B97
4	Model of pilot pressure controller valve		HUSCO 7480-75
5	(d*I)Dimension of lifting cylinder		Φ160*90*801(mm)
6	(D*I)Dimension of tilting cylinder		Φ210*110*494(mm)
Steering System			
1	Type	Middle articulated frame. full hydraulic power	
2	Model of steering pump	P360-G80467RD6G (for C6121)	P257-G80467HCX6/G40LIG (For Cummins)
3	Model of steering gear	BZZ ₃ -100	
5	System pressure	16MPa	
6	Dimension of steering cylinder	Φ100*50*425(mm)	
Brake System			
1	Type of traveling brake		Air assisted oil.4 wheel brake
2	Air pressure		0.7-0.8 (MPa)

2	Type of emergency brake	Manual control cutting-off air brake
3	Type of parking brake	inner expand hoof Automatic boosting. inner expand hoof
Oil Capacity		
1	Fuel(diesel)	350(L)
2	Engine lubricating oil	19(L)
3	Brake System	2 x 1.5(L)
4	Oil for converter and gear box	45(L)
5	Oil for hydraulic system	250(L)
6	Oil for driving axles (F/R)	70(L)+57(L)